

PL-MDS05-9W / PL-MDS06-15W

Our premium COB LED modules are available with either 9W or 15W output to suit a variety of installations. They are compatible with our wide range of downlight faces.

These energy efficient modules feature low-glare reflectors and a high CRI and are available with a range of beam angles. They are phase-dimmable, both leading and trailing edge.



700/1,000
770/1,250
790/1,300

LUMENS

9W
15W

WATT

2700K
3000K
4000K

COLOUR

IP20
IP44

IP RATING

50,000
HOURS

LIFETIME

15/24
38/55°


BEAM ANGLE

5 YEARS


WARRANTY

DIMMABLE


DIMMING



PL-MDS05-9W



PL-MDS06-15W



Accessories



Honeycomb



Snoot



Soft Beam Lens



Reflector
Titanium



Reflector
Bright Silver



Reflector
Matt Silver

Model	IP Rating	Power (W)	Lumen Output (lm)	CCT	CRI	Beam Angle	Dimming	Dimensions	Cut Out	Voltage	Colour
PL-MDS05-9W	IP20 IP44	9W	700lm 770lm 790lm	2700K 3000K 4000K	≥90	15° 24° 38° 55°	Dimmable	Ø55x49mm	N/A	200-240V AC	Black
PL-MDS06-15W		15W	1,000lm 1,250lm 1,300lm					Ø55x72mm			

LED MODULAR DOWNLIGHT SERIES

- Premium COB LED with high CRI, high efficiency and high illumination.
- Precision reflector ensures high-lumen output, even light distribution and low glare.
- Latest heat sink design, excellent heat dissipation.
- Easy to install and to adjust.
- Life span up to 50,000 hours.
- Various power options for different requirements.
- Wide range for both commercial and domestic installation.
- Anti-glare accessories available: honeycomb lens, snoot and soft beam lens.



LED MODULAR DOWNLIGHT SERIES

TYPE A



PL-MD51R
Ø85x52mm Ø 75mm



PL-MD52S
85x85x52mm 75x75mm



PL-MD53R
Ø105x58mm Ø 90mm



PL-MD54R
Ø115x62mm Ø 100mm


TYPE B




PL-MD01R
Ø88x48mm Ø 75mm



PL-MD02R
Ø88x48mm Ø 75mm



PL-MD03S
88x88x48mm Ø 75mm



PL-MD04S
88x88x48mm Ø 75mm



PL-MD05R
Ø88x48mm Ø 75mm

IP54



PL-MD06R
Ø88x48mm Ø 75mm



PL-MD07R
Ø88x64mm Ø 75mm



PL-MD08R
Ø88x68mm Ø 75mm




PL-MD09R
Ø88x40mm Ø 75mm




PL-MD10R
Ø88x47mm Ø 75mm



PL-MD11R
Ø88x48mm Ø 75mm



PL-MD12S
88x88x39mm 75x75mm



PL-MD13S
88x88x47mm 75x75mm




PL-MD14R
Ø105x48mm Ø 90mm



PL-MD15R
Ø105x48mm Ø 90mm


IP54




PL-MD16R
Ø105x48mm Ø 90mm



PL-MD17R
Ø82x23mm Ø 70mm




PL-MD18S
83x83x23mm Ø 70mm




PL-MD32S
88x88x48mm 75x75mm


IP54



PL-MD37R
Ø103x35mm Ø 90mm



PL-MD38S
103x103x35mm Ø 90mm




PL-MD39S
88x88x48mm Ø 75mm



PL-MD71R
Ø90x37mm Ø 80mm



PL-MD72S
90x90mm 80x80mm



PL-MD73S
175x90x37mm Ø165x80mm

LED MODULAR DOWNLIGHT SERIES

TYPE C



PL-MD20R
Ø85x17mm Ø 75mm



PL-MD25R
Ø85x90mm Ø 75mm



PL-MD27R
Ø85x30mm Ø 75mm



PL-MD29R
Ø96x27mm Ø 85mm



PL-MD30R
Ø104x35mm Ø 95mm



PL-MD31R
Ø108x49mm Ø 95mm

TYPE D



PL-MD41R
Ø75x45.5mm Ø 65mm



PL-MD42S
75x75x45.5mm Ø 65mm



PL-MD43R
Ø75x45.5mm Ø 65mm



PL-MD44S
75x75x45.5mm Ø 65mm



PL-MD45R
Ø85x45.5mm Ø 75mm



PL-MD46S
85x85x45.5mm Ø 75mm



PL-MD47R
Ø85x45.5mm Ø 75mm



PL-MD48S
85x85x45.5mm Ø 75mm

TYPE E



PL-MD61R
Ø102x58mm Ø 90mm



PL-MD62S
85x85x58mm 75x75mm