

## LG-NMS1217 (SIDE BEND) WHITE

- 12mm width flat luminous surface, applied for indoor & outdoor decorative lighting & architectural outdoor lighting, etc.
- High light efficacy, LM80 proved.
- Silicone extrusion process, IP67 protection level.
- Systematic installation solution for different installation requirements
- 3 years warranty (2 years for pixel), life span  $\geq 36000$ h



400lm/410m  
450lm/420m  
650lm  
LUMENS

9.6W/M  
12W/M  
TYPICAL WATT

2400K/2700K  
3000K/4000K  
CCT  
COLOUR


IP67  
IP RATING

24V  
DC


115°  
BEAM ANGLE

3  
YEARS  
WARRANTY


OPTIONAL  
DIMMING




### Accessories




**End Cap Set**  
LG-AS-NMS1217GH0-EC  
(L18 x W14 x H19mm)




**Top Connector**  
LG-AS-NMS1217HT0-FL  
(Wire: 500mm/ IP54)




**Bottom Connector**  
LG-AS-NMS1217HB0-FL  
(Wire: 500mm/ IP54)




**Left Connector**  
LG-AS-NMS1217HL0-FL  
(Wire: 500mm/ IP54)




**Right Connector**  
LG-AS-NMS1217HR0-FL  
(Wire: 500mm/ IP54)




**Quick Connector EC**  
LG-AS-NMS1217TX0-FL  
(IP54)



**Moldable Groove**  
LG-AS-NMS1217M-500  
(L500 x W13.1 x H11.9mm)



**Flat Al Carrier / Clip**  
LG-AS-NMS1217A-1000/25  
(L1000/25 x W14.4 x H18.85mm)



**Reserved Al Carrier / Clip**  
LG-AS-NMS1217A1-1000/25  
(L1000/25 x W14.4 x H24.85mm)

IK08



Model	IP Rating	Typical Power (W/M)	Max Power (W/M)	Lumen Output (lm)	CCT	CRI	Beam Angle	Dimming	Cuttable (mm)	Dimensions	Voltage	Bend Radius
LG-NMS1217	IP67	9.6W/M	10.6W/M	400lm/M 410lm/M 430lm/M 430lm/M	2400K 2700K 3000K 4000K	$\geq 90$	115°	Optional	7LED 50mm	12x17mm	24V DC	$\geq 60$ mm
		12W/M	14W/M	650lm/M	CCT (2700~6000K)	$\geq 80$			14LED 100mm			