

LG-NJS0612 (SIDE BEND)

- Slender with trims, profile-free easy installation;
- Reel-to-reel processed light source, LM80 proved;
- Integrated silicone extrusion molded, UL, CE and ROHS certificated;
- Featured in IP65, suitable for interior outline and auxiliary lighting;
- 3-year indoor and 2-year outdoor warranty, life span \geq 36000 hrs.



340lm/M

LUMENS

8.8W/M

TYPICAL WATT

4000K

COLOUR

IP65

IP RATING

24V

DC

115°


BEAM ANGLE

**3
YEARS**


WARRANTY

OPTIONAL


DIMMING




Accessories




End Cap Set
LG-AS-NMS0612GS0-EC
(L18 x W14 x H19mm)



Moldable Groove
LG-AS-NMS0612M-500
(L500 x W7.3 x H10.6mm)



Reserved Al Carrier / Clip
LG-AS-NMS0612A1-1000/20
(L1000/20 x W8 x H18.5mm)



Flat Al Carrier / Clip
LG-AS-NMS0612A-1000/20
(L1000/20 x W8 x H13.5mm)

IK06



Model	IP Rating	Typical Power (W/M)	Max Power (W/M)	Lumen Output (lm)	CCT	CRI	Beam Angle	Dimming	Cutttable (mm)	Dimensions	Voltage	Bend Radius
LG-NJS0612	IP65	8.8W/M	9.6W/M	340lm/M	4000K	\geq 80	115°	Optional	6LED 50mm	12x6mm	24V DC	\geq 30 mm