

LG-NJT1010 (TOP BEND)

- Uniform and soft lighting with no shadow;
- Reel-to-reel processed light source, LM80 proved;
- Integrated silicone extrusion molded, UL, CE and ROHS certificated;
- Featured in IP65, suitable for interior outline and auxiliary lighting;
- 3-year indoor and 2-year outdoor warranty, life span \geq 36000 hrs



740lm/M
770lm/M

LUMENS

8.8W/M

TYPICAL WATT

3000K
4000K

COLOUR

IP65

IP RATING

24V

DC

115°


BEAM ANGLE

3
YEARS

WARRANTY

OPTIONAL


DIMMING




Accessories



End Cap Set
LG-AS-NMT1010GS0-EC
(L12 x W12 x H15mm)



Flat Al Carrier / Clip
LG-AS-NMT1010A-1000/20
(L1000/20 x W12 x H11mm)



Moldable Groove
LG-AS-FR-S1010-005
(L1000 x W10.9 x H10.03mm)

IK08



Model	IP Rating	Typical Power (W/M)	Max Power (W/M)	Lumen Output (lm)	CCT	CRI	Beam Angle	Dimming	Cutttable (mm)	Dimensions	Voltage	Bend Radius
LG-NJT1010	IP65	8.8W/M	9.6W/M	740lm/M 770lm/M	3000K 4000K	\geq 80	115°	Optional	6LED 50mm	10x10mm	24V DC	\geq 60 mm